



CERT

DIN-DVGW type examination certificate

DIN-DVGW-Baumusterprüfzertifikat

NV-5142BL0134

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas and water supply <i>Produkte der Gas- und Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viscotex Schmiertechnik AG Industriestrasse 19, CH-9450 Altstätten
Distributor <i>Vertreiber</i>	Viscotex Schmiertechnik AG Industriestrasse 19, CH-9450 Altstätten
Product Category <i>Produktart</i>	greasing and sealing materials: Sealing and jointing materials for gas and water installations for metallic jointing, non hardening (5142)
Product Description <i>Produktbezeichnung</i>	Non hardening thread sealing compound
Model <i>Modell</i>	Locher Paste 2000
Test Reports <i>Prüfberichte</i>	laboratory control test: 15/125/5142/01 from 18.05.2015 (EBI) KTW testing: K-260443-15-Ko/st from 18.08.2015 (WHY)
Test Basis <i>Prüfgrundlagen</i>	DIN EN 751-2 (01.08.1997) DIN 30660 (01.12.1999) UBA KTW (16.05.2007)

Date of Expiry / File No. 25.04.2020 / 18-0176-GNU
Ablaufdatum / Aktenzeichen

23.02.2018 Fi A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888

Fax +49 228 91 88 - 993

www.dvgw-cert.com

info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Locher Paste 2000	class: ARp	

Hints of Utilization / Remarks***Verwendungshinweise / Bemerkungen***

Range of temperature/pressure (gas): -20 °C up to +70 °C / <= 5 bar

Range of temperature/pressure (drinking water): up to +23 °C / <= 16 bar

Range of temperature/pressure (hot water): up to +130 °C / <= 7 bar

Sealing material of the class ARp; the restricted turning back of conical respectively cylindrical thread connections up to 45° is possible

Application: non hardening thread sealing compound only to use in combination with hemp